

JUPITER T6

8 Seats Minibus







A/C control



AM/FM radio with MP3 port



2nd row seats
(with 1 folding seat)




3-spoke steering wheel



Front power windows

AM/FM radio with MP3 port

Engine



LJ474Q3E2
4-cylinder in-line
16-valve, DOHC, EFI
1298cc, gasoline
60.5kw/6000rpm
Euro 4
**CNG & gasoline dual
fuel as option**



DA465QA
4-cylinder in-line
16-valve, EFI
970cc, gasoline
44kw/5500rpm
Euro 3

2nd row seats
(with 1 folding seat)

SPECIFICATIONS

Model	STJ6400A		STJ6400B
Vehicle type	Minibus		
DIMENSION & WEIGHTS			
Overall dimension (mm)	Length	4030	
	Width	1620	
	Height	1900	
Wheelbase	(mm)	2700	
Ground clearance	(mm)	153	
Tread, front/rear	(mm)	1386/1408	
Approac/ departure angle	(°)	25/35	
Curb vehicle weight	(kg)	1178	
Payload	(kg)	670	
Gross vehicle weight	(kg)	1850	
Seating capacity	(persons)	8	
ENGINE			
Engine	Model	LJ474Q3E2	DA465QA
	Type	Gasoline, 4-cylinder in-line, 16-valve, DOHC, EFI	Gasoline, 4-cylinder in-line, 16-valve, EFI
Displacement	(cc)	1298	970
Max. power	(kw/rpm)	60.5/6000	44/5500

FEATURES

A/C & Audio	Dual-evaporators A/C + power front windows	<input type="checkbox"/>
	Radio + MP3 USB port	<input checked="" type="checkbox"/>
	CD player	–
Exterior	Steel wheels	<input checked="" type="checkbox"/>
	Aluminum alloy wheel	–
	Bumper in color of vehicle body	<input checked="" type="checkbox"/>
	Outside door handle with chromium-plated	–
	Outside rear spoiler	–
Interior	8 seats (2+3+3), with 1 folding seat for 2nd row	<input checked="" type="checkbox"/>
	Headrests for all seats except for folding seat & middle seat of 3rd row	<input checked="" type="checkbox"/>
	2 separate, sliding seats for the 2nd row seat	–
	Seat belts for all seats	<input checked="" type="checkbox"/>
	Sun visor with mirror	<input checked="" type="checkbox"/>
	Combination instrument with ABS & EBD indicator	–
	Inner door handle with chromium-plated	–
	Side window open switch	<input checked="" type="checkbox"/>
	Front fog lights	<input checked="" type="checkbox"/>
	High-mounted brake lamps	<input checked="" type="checkbox"/>
	Middle door child-proof lock	<input checked="" type="checkbox"/>

Max. torque	(N.m/rpm)	102	102
Max. vehicle speed	(km/h)	135	120
Emission		Euro 4	Euro3
Fuel consumption	(L/100km)	6.5	
DRIVE TRAIN			
Clutch		Diaphragm spring	
Transmission		5 speed manual	
CHASSIS			
Suspension	Front	Mac Pherson strut Independent suspension	
	Rear	Leaf springs	
Brake	Front/rear	Disc/Drum	
Steering		Mechanical recirculating ball	
Max. grade ability	(°)	≥25	
Tires		175/70R14 LT	

Safety	Crumple-steering column	■
	Steering column lock	■
	Anti-sliding door lock	■
	Remote control central lock	□
	ABS +EBD	□
	Airbag for driver	□
	Back up radar	□
	Power steering	-

Note: ■ = Standard □ = Optional - = Not available

SPECIFICATIONS		
Model		STJ6402A
Vehicle type		Minibus
DIMENSION & WEIGHTS		
Overall dimension (mm)	Length	4030
	Width	1620
	Height	1900
Wheelbase	(mm)	2700
Ground clearance	(mm)	157
Tread, front/rear	(mm)	1386/1408
Approac/ departure angle	(°)	25/35
Curb vehicle weight	(kg)	1268
Payload	(kg)	670
Gross vehicle weight	(kg)	1850

FEATURES		
A/C & Audio	Dual-evaporators A/C + power front windows	□
	Radio + MP3 USB port	■
	CD player	-
Exterior	Steel wheels	■
	Aluminum alloy wheel	-
	Bumper in color of vehicle body	■
	Outside door handle with chromium-plated	-
	Outside rear spoiler	-
Interior	8 seats (2+3+3), with 1 folding seat for 2nd row	■
	Headrests for all seats except for folding seat & middle seat of 3rd row	■
	2 separate, sliding seats for the 2nd row seat	-
	Seat belts for all seats	■

Seating capacity	(persons)	8
ENGINE		
Engine	Model	LJ474Q3E2 + CNG
	Type	Gasoline, 4-cylinder in-line, 16-valve, DOHC, EFI, & with CNG (80L/tank)
Displacement	(cc)	1298
Max. power	(kw/rpm)	60.5kw/6000; 54.3kw
Max. torque	(N.m/rpm)	102 (gasoline); 91.8 (CNG)
Max. vehicle speed	(km/h)	135 (gasoline); 110 (CNG)
Emission		Euro 4
Fuel consumption	(L/100km)	6.5 (gasoline)
DRIVE TRAIN		
Clutch		Diaphragm spring
Transmission		5 speed manual
CHASSIS		
Suspension	Front	Mac Pherson strut Independent suspension
	Rear	Leaf springs
Brake	Front/rear	Disc/Drum
Steering		Mechanical recirculating ball
Max. grade ability	(°)	≥25
Tires		175/70R14 LT

Safety	Sun visor with mirror	■
	Combination instrument with ABS & EBD indicator	-
	Inner door handle with chromium-plated	-
	Side window open switch	■
	Front fog lights	■
	High-mounted brake lamps	■
	Middle door child-proof lock	■
	Crumple-steering column	■
	Steering column lock	■
	Anti-sliding door lock	■
	Remote control central lock	□
	ABS +EBD	□
	Airbag for driver	□
	Back up radar	□
	Power steering	-

Note: ■ = Standard □ = Optional - = Not available



KINGSTAR VEHICLE CO., LTD.

<http://www.kingstar.com.cn>

E-mail: info@kingstar.com.cn