

MARS Z2

Pickup



2012

**MARS Z2** pickup is designed according to latest trend of development, and in step with TUNDRA, NISSAN FRONTIER, which are TOYOTA's car models currently sold well in North America. Also, **MARS Z2** pickup, TUNDRA, and NISSAN FRONTIER all belong to the fifth generation of pickup models. **MARS Z2** Pickup embodies newest technologies and designing theories. Keeping in step with the newest car models developed by the international market.

**MARS Z2** Pickup depends on first grade global auto components purchasing system, equipped with most technically mature high-tech auto components. By selecting and using necessary accessories made by world famous brands such as TOYOTA and NISSAN, the quality of entire autos is in step with trend of world development.



KINGSTAR VEHICLE CO., LTD.

<http://www.kingstar.com.cn>

E-mail: [info@kingstar.com.cn](mailto:info@kingstar.com.cn)

## EXTERIOR & INTERIOR



SPECIFICATIONS			
Fuel Type	Gasoline		Diesel
Cabin type	Single Cab		
Model	BQ1023RDY2V		BQ1023DN8V
Driving type	2WD		
DIMENSION & WEIGHT			
Overall length	(mm)	5080	
Overall width	(mm)	1750	
Overall height	(mm)	1710	
Wheelbase	(mm)	2900	
Tread, front/rear	(mm)	840/1340	
Cargo body inside	(mm)	2180x1505x480	
Ground clearance	(mm)	≥191	
Approach/ departure angle	(°)	≥32/≥17	
Curb vehicle weight	(kg)	1445	
Gross vehicle weight	(kg)	2325	
Seating capacity	(persons)	2	
Fuel tank capacity	(L)	60	
SYSTEM			
Gearbox	5 speed manual, floor shift		
Steering	Circulating-ball, power-assisted		
Suspension	Front	Dual arms with torsion bar springs independent suspension, with telescopic shock	
	Rear	Variable rate asymmetric leaf springs	
Braking, front/rear	Ventilated disc/Leading & trailing drums		
Clutch	Single plate, dry type diaphragm spring with tensional vibration damper		
Min. turning radius	(m)	≤12.5	
Tires	215/75R15		
Max. vehicle speed	(km/h)	130	
ENGINE			
Model	491Q-ME		4JB1T
Type	Gasoline, 4-cylinder, 4-stroke, direct fuel injection, Separated Sequence MFI Muhipoint Fuel Injection		Diesel, 4-cylinder, 4-stroke, turbo--charge inter-cooler, Direct Fuel Injection
Technology source	TOYOTA		ISUZU
Displacement	(cc)	2237	
Max. power	(kw/rpm)	76/4200-4600	
Max. torque	(N.m/rpm)	193/2000~2600	
Compession ratio	8.8:1		17.5:1
Fuel consumption	(L/100KM)	≤11.5	
Emission standard	EuroII		Euro III

FEATURES		
Chassis	Wheel discs	Steel
	Spare tire	■ Steel
	Tire	215/75R15
	Power steering	■
	Load sensitive proportion valve (SABS)	■
Functions	Environmental A/C	■
	Mechanical lock	■
	Adjustable steering column	■
	Single disc CD player	■
	Engine tachometer	■
	Outside manual rear view mirrors	■
	Power windows	■
Body	Head	New face style with front bumper
	Metallic paint	□
	Rail of cargo	■
	Rear bumper	■
	Wheel eyebrow	■
	Bottom beam plate	■
	Cargo deck	New style
	Plastic paint cover for cargo deck	■
	High-mounted lamp	—
Inner trim	Interior trim color	Grey
	Glare-free Interior review mirror	■
	Fabric seats	■

**Note:** ■ = Standard □ = Optional - = Not available